


różnorodność modeli



możliwość cięcia  
co 25mm lub 50mm



wodoszczelna osłona



kod



EAN



barwa światła [K]

$P_{ON}/1m$

pobór mocy [W]



strumień świetlny [lm]



długość [m]



klasa energetyczna

D87-LS-2835-3000-IP20-AWW

5900280940322

biała ciepła

4.8

600

50

G

D87-LS-2835-3000-IP20-ANW

5900280940933

biała neutralna

4.8

620

50

G

D87-LS-2835-3000-IP20-ACW

5900280940940

biała zimna

4.8

640

50

G

D87-LS-2835-300-IP20-AWW

5900280930286

biała ciepła

4.8

450

5

G

D87-LS-2835-300-IP20-ANW

5900280940544

biała neutralna

4.8

470

5

G

D87-LS-2835-300-IP20-ACW

5900280930279

biała zimna

4.8

490

5

G

D87-LS-2835-300-IP65-AWW

5900280930309

biała ciepła

4.8

440

5

G

D87-LS-2835-300-IP65-ANW

5900280944443

biała neutralna

4.8

450

5

G

D87-LS-2835-300-IP65-ACW

5900280930293

biała zimna

4.8

460

5

G

D87-LS-2835-6000-IP20-AWW

5900280936530

biała ciepła

9.6

870

50

G

D87-LS-2835-6000-IP20-ANW

5900280940926

biała neutralna

9.6

900

50

G

D87-LS-2835-6000-IP20-ACW

5900280934000

biała zimna

9.6

930

50

G

D87-LS-2835-600-IP20-AWW

5900280944405

biała ciepła

9.6

870

5

G

D87-LS-2835-600-IP20-ANW

5900280944399

biała neutralna

9.6

900

5

G

D87-LS-2835-600-IP20-ACW

5900280944382

biała zimna

9.6

930

5

G

D87-LS-2835-600-IP65-AWW

5900280944436

biała ciepła

9.6

810

5

G

D87-LS-2835-600-IP65-ANW

5900280944429

biała neutralna

9.6

840

5

G

D87-LS-2835-600-IP65-ACW

5900280944412

biała zimna

9.6

870

5

G