

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR WYŁĄCZNIK

DETAILED CARD



TECHNICAL PARAMETERS

Index:	247040
Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	32
Supply voltage [V]:	220-240
Luminous flux [lm]*:	4300
Energy efficiency class:	D
Electrical protection class:	I
Colour temperature [K]:	4000

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle. A rubber cable H07RN-F 3x1.5 mm2 (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE 32W I KL. OCHR. SZARY Z GNIAZDAMI PL-FR WYŁĄCZNIK

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Impact resistance:	IK10
Nominal power [W]:	32	Ingress protection:	IP54
Supply voltage [V]:	220-240	Plug type:	UNI-SCHUKO
Luminous flux [lm]:	4300	Socket type:	PL-FR
Energy efficiency class:	D	Sockets:	2
Electrical protection class:	I	Cable length [m]:	5
Colour temperature [K]:	4000	Switch:	yes
Beam angle [°]:	120	Net weight of the luminaire [kg]:	2.900
Diffuser material:	PC	Index:	247040
Diffuser type:	frozen	Category type:	workplace floodlights
Material of the body:	PP	ETIM class:	EC000347
Colour of the body:	grey	Manual:	Download PDF
Dimensions (H/W/T/S) [mm]:	300/400/100		

Card creation date: 03 January 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 75/2020



Lena Lighting S.A.
ul. Kórnicka 52, 63-000 Środa Wielkopolska
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl