

MAGNUM FUTURE 20W 45 ST Z GNIAZDEM PL-FR

DETAILED CARD



TECHNICAL PARAMETERS

Index:	248535
Ingress protection:	IP54
Impact resistance:	IK10
Nominal power [W]:	20
Colour temperature [K]:	4000
Luminous flux [lm]*:	2300
Supply voltage [V]:	220-240
Electrical protection class:	I
Material of the body:	PP
Colour of the body:	grey

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Made of impact-resistant polipropylene (PP). Anti-glare diffuser which transmits up to 80% of the light emitted by the diodes. The smaller size and compact design make it convenient to transport. It is equipped with a movable, multi-position arm also acting as a hook. Multi-purpose mounting bracket included.

It can be mounted on a Future Stand, significantly increasing the range and comfort of use.

APPLICATION

It can be used as a workplace luminaire to illuminate workplaces, workshops or garages.

MAGNUM FUTURE 20W 45 ST Z GNIAZDEM PL-FR

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Light source:	LED module	Plug type:	UNI-SCHUKO
Nominal power [W]:	20	Socket type:	PL-FR
Colour temperature [K]:	4000	Sockets:	1
Luminous flux [lm]:	2300	Cable length [m]:	3
Supply voltage [V]:	220-240	Net weight of the luminaire [kg]:	1
Electrical protection class:	I	Index:	248535
Beam angle [°]:	45	Category type:	workplace floodlights
Diffuser material:	PC	Dimensions (H/W/T/S) [mm]:	192/193/123
Diffuser type:	frozen	Energy efficiency class:	D
Material of the body:	PP	ETIM class:	EC000347
Colour of the body:	grey	CE certificate:	126/2021
Impact resistance:	IK10	Manual:	Download PDF
Ingress protection:	IP54		

Card creation date: 24 September 2020

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 126/2021