

MAGNUM FUTURE 105W I PROTECTION CLASS WITH PL-FR SOCKETS

DETAILED CARD



TECHNICAL PARAMETERS

Ingress protection:	IP54
Impact resistance:	IK10
Rated power of the luminaire [W]*:	105
Colour temperature [K]:	4000
Luminous flux [lm]*:	14055
Supply voltage [V]:	220-240
Energy efficiency class:	E
Electrical protection class:	I
Colour of the body:	grey
Diffuser material:	PC

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.

A rubber cable H07RN-F 3x1,5 mm² (5 m) comes as standard.

APPLICATION

With a variety of functions, the lamp is ideal for illuminating any workplace. The high luminous flux and maximum degree of impact resistance are especially important for lighting construction sites or for the work of services intervening in various emergencies. A high degree of waterproofness allows its use in the harshest weather conditions. The multi-position arm and numerous accessories provide a wide range of mounting options so as to precisely direct the light beam, leaving the worker's hands free. Its small size and light weight make it easy to use in workshops, car showrooms, to illuminate the workplace in industrial halls or finishing work.

MAGNUM FUTURE 105W I PROTECTION CLASS WITH PL-FR SOCKETS

DETAILED CARD

TECHNICAL PARAMETERS TABLE

Index:	244568	Diffuser colour:	white
EAN:	5905963244568	Colour of the body:	grey
Light source:	LED module	Dimensions (H/W/T/S) [mm]:	300/480/75
Rated power of the luminaire [W]:	105	Impact resistance:	IK10
Colour temperature [K]:	4000	Ingress protection:	IP54
Luminous flux [lm]:	14055	Plug type:	UNI-SCHUKO
Supply voltage [V]:	220-240	Socket type:	PL-FR
Frequency [Hz]:	50-60	Sockets:	2
Luminous efficacy [lm/W]:	134	Wire type:	H07RN-3x1.5mm ²
Energy efficiency class:	E	Cable length [m]:	5
Electrical protection class:	I	Net weight of the luminaire [kg]:	3.600
Colour rendering index:	>80	Category type:	workplace floodlights
Diffuser material:	PC	Manual:	Download PDF
Diffuser type:	MAT	CE certificate:	68/2022

Card creation date: 12 July 2022

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. * Parameter tolerance is +/- 10%



This product is a subject to electric and electronic waste equipment regulations (WEEE).



Certificate CE - Nr: 68/2022