



INDEX: 04113
PASO LED 9W BLACK NW
Decorative SMD LED fitting

Power	9 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1140 lm
Colour	black/gold	IP	44
Luminous beam angle	120°	Dimensions [mm]	25 / 395 / 120
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04114
PASO LED 12W WHITE NW
Decorative SMD LED fitting

Power	12 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1480 lm
Colour	white/chrom	IP	44
Luminous beam angle	120°	Dimensions [mm]	25 / 500 / 120
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04115
PASO LED 12W BLACK NW
Decorative SMD LED fitting

Power	12 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1480 lm
Colour	black/gold	IP	44
Luminous beam angle	120°	Dimensions [mm]	25 / 500 / 120
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04139
PASO LED 14W WHITE NW
Decorative SMD LED fitting

Power	14 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1680 lm
Colour	white/chrom	IP	44
Luminous beam angle	120°	Dimensions [mm]	25 / 600 / 120
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04140
PASO LED 14W BLACK NW
Decorative SMD LED fitting

Power	14 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1680 lm
Colour	black/gold	IP	44
Luminous beam angle	120°	Dimensions [mm]	25 / 600 / 120
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 03847
PRYMUS LED 7W BLACK NW
Decorative SMD LED fitting

Power	7 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	870 lm
Colour	black/gold	IP	44
Luminous beam angle	120°	Dimensions [mm]	50 / 430 / 135
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04020
PRYMUS LED 12W BLACK NW
Decorative SMD LED fitting

Power	12 W	Power Supply	230V 50Hz
Light colour	neutral white	Temperature	4100K
Light source	SMD LED, in set	Luminous flux	1430 lm
Colour	black/gold	IP	44
Luminous beam angle	120°	Dimensions [mm]	50 / 630 / 135
Material	stainless steel, polycarbonate PC		
Comments	for operation in increased-humidity locations, e.g. bathrooms; driver included		



INDEX: 04134
SEWERYN LED 1,6W NW
Under-cupboard linear SMD LED fitting

Power	1,6 W	Power Supply	DC 5 V 2,1 A MAX USB-C
Light colour	neutral white	Temperature	4300K
Light source	LED, in set	Luminous flux	205 lm
Colour	silver	IP	20
Luminous beam angle	120°	On/off switch	yes
Dimensions [mm]	8 / 320 / 40		
Material	aluminium, plastic		
Comments	with PIR motion sensor; works with ambient light below 50lx; range 60°; maximum motion detection range is 2m (<24°); lighting time 20s		



INDEX: 04135
SEWERYN LED 2,3W NW
Under-cupboard linear SMD LED fitting

Power	2,3 W	Power Supply	DC 5 V 2,1 A MAX USB-C
Light colour	neutral white	Temperature	4300K
Light source	LED, in set	Luminous flux	265 lm
Colour	silver	IP	20
Luminous beam angle	120°	On/off switch	yes
Dimensions [mm]	8 / 400 / 40		
Material	aluminium, plastic		
Comments	with PIR motion sensor; works with ambient light below 50lx; range 60°; maximum motion detection range is 2m (<24°); lighting time 20s		