

### **ROXANA LED 5W CHROME 4000K**

#### DECORATIVE SMD LED FITTING

#### O MATERIAL

- O DIMENSIONS [mm]
- ALUMINIUM
- \$ 111 ↔ 300 🖍 39
- O COLOUR

#### O COMMENTS



03748

PRODUCT CODE



FOR OPERATION IN INCREASED-HUMIDITY LOCATIONS, E.G. BATHROOMS







#### Product specifications



Power supply 220-240V~



Non-replaceable light source





Light source life 30000



Light colour neutral white 4000K





For use indoors only



Multipack pcs 20



Power 5 W





Without regulation of lighting direction





Luminous flux distribution angle 110°





Minimum distance from a lit object 0.5m



Certificate



Light source SMD LED, in set



Luminous flux 330 lm



The degree of resistance to dust and moisture IP44



Colour rendering index Ra >80



Electric shock protection Class 2





#### **ROXANA LED** 13W CHROME 4000K

#### DECORATIVE SMD LED FITTING

#### O MATERIAL

- O DIMENSIONS [mm] \$ 111 ↔ 600 🖍 39
- ALUMINIUM • GLASS
- O COLOUR
- CHROME

#### O COMMENTS

FOR OPERATION IN INCREASED-HUMIDITY LOCATIONS, E.G. BATHROOMS

# PRODUCT CODE 03749

# 













### Product specifications



Power supply 220-240V~



Non-replaceable light source



Light source life 30000



neutral white 4000K



For use indoors only



Multipack pcs



Power 13 W







Without regulation of lighting direction



Luminous flux distribution angle





Minimum distance from a lit object 0.5m



Certificate



Light source SMD LED, in set



Luminous flux 845 lm



The degree of resistance to dust and moisture IP44



Colour rendering index Ra >80



Electric shock protection Class 2



# **ROXANA LED** 15W CHROME 4000K

# DECORATIVE SMD LED FITTING

#### O MATERIAL

ALUMINIUM

O COMMENTS

O DIMENSIONS [mm]

111 ↔ 900 🖍 39

GLASS

CHROME

O COLOUR

FOR OPERATION IN INCREASED-HUMIDITY LOCATIONS, E.G. BATHROOMS

# ENERGY LABEL

PRODUCT CODE 03750







# Product specifications



Power supply 220-240V~



Non-replaceable light source



Light source life 30000





Light colour neutral white 4000K



For use indoors only



Multipack pcs 20



Power 15 W





Without regulation of lighting direction



Luminous flux distribution angle 110°



Minimum distance from a lit object 0.5m



Certificate



SMD LED, in set



Luminous flux 968 lm



The degree of resistance to dust and moisture IP44



Colour rendering index Ra > 80



Electric shock protection Class 2