OVAL LED PRO

LED GO!





TECHNICAL PARAMETERS

Ingress protection:	IP44;
Impact resistance:	IK10;
Nominal power [W]:	3.40;
Luminous flux [lm]*:	370;
Colour temperature [K]:	4000;
Energy efficiency class:	A;
Material of the body:	PP;
Diffuser material:	PC;
Diffuser type:	OPAL;
Mounting version:	surface;
Dimensions [mm]:	160/85/45;

*Tolerance +/- 10%

CHARACTERISTICS

Surface-mounted, modern technical bulkhead suitable for installing on walls and ceilings. Its design allows surface mounted wiring as well as through wiring. Avilable in 4W version, with 360 lumens light output. Equipped with an opal diffuser made of Makrolon® LED (Bayer) providing excellent dispersion and allowing up to 93% light transmission. The unique, patented design, includes direct installation of LED panels on the diffuser. The diffuser is connected to the base on a movable hinge, which provides easy access to the terminal block and mounting points of the lamp. The fitting is highly impact-resistant IK10 and has ingress protection class IP44

APPLICATION

Dedicated for both indoor (rooms with high humidity, passageways, staircases and basements) and outdoor use (industrial façade lighting, car parks). Easy access to mounting points. Through-wiring system. Gaskets. Easy access to terminal lock. Easy access to the mounting holes. Installation of LED GO! panels directly on the diffuser.



OVAL LED PRO



AVAILABLE TYPES


Click >> index, to see details

Nominal power [W]	Colour temperature [K]	Luminous flux [lm]*	Diffuser type	Energy efficiency class	Index
3.40	4000	370	OPAL	Α	<u>>> 233548</u>

*Tolerance +/- 10%

LUMINOUS INTENSITY DISTRIB. CURVE

OVAL LED PRO 3,4W




The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.











This product is a subject to electric and electronic waste equipment regulations (WEEE).

