


connecting the future



TOU - 1 outlet R/TV terminated

Article number: 303621

Product description:

TOU - 1 terminated

The Triax TOU series of outlets is made of diecast zinc, the coax IEC connectors fulfil the DIN 45325 and IEC 169 standards. The outlets can be built into a Ø60 mm round wall box or surface mounted by means of a TOU frame.

Specifications

ORDER INFORMATION	
EAN Number	5702663036215
SHIELDING	
Shielding factor UHF	> 75.0 dB
Shielding factor VHF	> 85.0 dB
CHARACTERISTICS	
Outlet Type	Terminated
FREQUENCY	
Frequency Range FM	87.5...108 MHz
Frequency Range TV	5...74/120...862 MHz

LOSS	
Through Loss IN-FM	2.0 dB
Through Loss IN-TV	1.5 dB
ISOLATION	
Isolation TV-FM	>10.0 dB
RETURN LOSS	
Return Loss FM	Cat. D *) EN 50083-4 dB
Return loss SAT	Cat. D *) EN 50083-4 dB
Return Loss TV	Cat. C *) EN 50083-4 dB
ELECTRICAL	
Impedance	75 Ω
CONNECTORS	
Connector FM	IEC-female
Connector TV	IEC-male
MECHANICAL	
Diameter	60 mm
Packaging Depth	0,070 m
Packaging Height	0,040 m
Total Weight	0,115 kg
Packaging Width	0,070 m
Net Weight	0,098 kg
Remarks	*) According to CENELEC: B: 5-40 MHz > 18 dB, 40-862 MHz min. 18 dB - 1.5/oct. C: 5-40 MHz > 14 dB, 40-862 MHz min. 14 dB - 1.5/oct. D: 5-862 MHz > 10 dB. Standards CE: EN 50083-4. NB! excl. cover and
Tara Weight	0,017 kg
Weight (kg)	0 kg