




connecting the future

TRIAX



TOU - 01S outlet R/TV/SAT terminated

Article number: 303693

Product description:

TOU - 01S terminated

The TRIAX TOU series of outlets is made of diecast zinc, the coax IEC connectors fulfil the DIN 45325 and IEC 169 standards. The outlets can be built into a Ø60 mm round wall box or surface mounted by means of a TOU frame.

Specifications

ORDER INFORMATION	
EAN Number	5702663036932
SHIELDING	
Shielding factor UHF	>75 dB
Shielding factor VHF	>85 dB
CHARACTERISTICS	
Type	TOU
Outlet Type	Terminated

FREQUENCY	
Frequency Range FM	87.5...108 MHz
Frequency Range TV	5...74/120...862 MHz
Frequency Range SAT	950...2250 MHz
LOSS	
Through Loss IN-FM	1.5 dB
Through Loss IN-TV	2.0 dB
Through Loss IN-SAT	2.0 dB
ISOLATION	
Isolation FM-SAT	> 40.0 dB
Isolation TV-FM	>15.0 dB
RETURN LOSS	
Return Loss FM	Cat. D *) dB
Return Loss TV	Cat. C *) dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
Screening Efficiency	EN50083-2 (Class A)
DC Passthrough SAT	Yes (20VDC / 500mA)
CONNECTORS	
Connector IN	Saddle & Clamp (S&C)
Connector FM	IEC-female
Connector TV	IEC-male
MECHANICAL	
Diameter	60 mm
Dimensions product (H x D x W)	70.6 x 70.6 x 21,9 mm
Packaging Height	0,040 m
Packaging Width	0,070 m
Packaging Depth	0,070 m
Net Weight	0,102 kg

Tara Weight	0,015 kg
Total Weight	0,117 kg
Remarks	*) According to CENELEC: C: 5-40 MHz > 14 dB, 40-862 MHz min. 14 dB - 1.5/oct. D: 5-862 MHz > 10 dB.
